SOP of Plasma Asher

- 1. Book the online slot before using the plasma asher.
- 2. Activate the slot and fill the logbook.
- 3. Oxygen cylinder main knob is kept closed so, open that using the key.
- 4. Vent the chamber
- 5. Arrange samples on the substrate holder.
- 6. Close and hold the chamber door, turn
- 7. PUMP ON, GAUGE ON
- 8. Wait till pressure reaches 0.05 mbar and note that time in the logbook.
- 9. Turn knob slowly \leftarrow , O_2 will be released.
- 10. Wait till pressure reaches 0.5 mbar.
- 11. PLASMA ON, RF power ON, wait 20 seconds, turn RF level OFF to HI slowly. (Wait a few seconds for the plasma to come.)

After Ashing (max 10 min)

- 12. Turn HI to OFF, RF power OFF, PLASMA OFF.
- 13. Turn , Wait for 30 sec.
- 14. PUMP OFF.
- 15. Vent the chamber very slowly
- 16. Take the samples out, keep substrate holder inside.
- 17. Close and hold the chamber door, turn
- 18. PUMP ON (for 1 min)
- 19. PUMP OFF, GAUGE OFF.
- 20. Close the main cylinder knob using the key after every process.

IMP NOTE:

- Don't disturb any setting in the plasma asher. Don't disturb regulator of the cylinder.
- **Don't forget to turn off the pump.**